

Product information sheet

LED Colour MR16 GU5.3 12V 5.5W Blue 40D

Bailey nr.: 142071

EAN-code: 8714681420713

Type of light source

| | |
|--------------------------------|-------|
| Lighting technology used | LED |
| Cap type | GU5.3 |
| Non-directional or directional | DLS |
| Mains or non-mains | NMLS |
| Connected light source (CLS) | No |
| Colour-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Dimmable | No |



Specifications

| | |
|---|-------------------|
| Energy consumption in on-mode (KWh/1000h) | 6 |
| Energy Efficiency Class | N/A |
| Useful luminous flux (use) in lm | - |
| Beam angle correspondence | Narrow cone (90°) |
| Correlated colour temperature (K) | Blue |
| On-mode power (Pon) in W | 5,5 |
| Standby power (Psb) in W | 0,00 |
| Networked standby power for CLS (Pnet) in W | - |
| Colour rendering index | N/A |
| Outer dimension (Height) in mm | 50 |
| Outer dimensions (Width) in mm | 50 |
| Outer dimensions (Depth) in mm | - |
| Claim of equivalent power | No |
| Equivalent power (W) | - |
| Chromaticity coordinate (x) | 0,145 |
| Chromaticity coordinate (y) | 0,030 |
| Peak luminous intensity (cd) | - |
| Beam angle (°) | 40 |
| R9 Colour rendering index | - |
| Survival factor | - |
| Lumen maintenance factor | - |
| Displacement factor | N/A |
| Colour consistency in McAdam ellipses | N/A |
| Claim CFL-ni | No |
| Replacement claim (W) | - |
| Flicker metric | N/A |
| Stroboscopic effect metric | N/A |
| Lifetime L70B50 (h) | 40000 |
| Nominal voltage (V) | 12 |
| Voltage type | AC/DC |
| Frequency | - |

Specific precautions N/A

Spectral power distribution