

Product information sheet

LED Batten Basic 1500 45W 4000K IP65

Bailey nr.: 142308

EAN-code: 8714681423080

Type of light source

Lighting technology used	LED
Cap type	-
Non-directional or directional	DLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



Specifications

Energy consumption in on-mode (KWh/1000h)	45
Energy Efficiency Class	F
Useful luminous flux (use) in lm	3650
Beam angle correspondence	Wide cone (120°)
Correlated colour temperature (K)	4000
On-mode power (Pon) in W	45,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	1517
Outer dimensions (Width) in mm	82
Outer dimensions (Depth) in mm	47
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	-
Chromaticity coordinate (y)	-
Peak luminous intensity (cd)	-
Beam angle (°)	120
R9 Colour rendering index	-
Survival factor	-
Lumen maintenance factor	-
Displacement factor	-
Colour consistency in McAdam ellipses	-
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	-
Stroboscopic effect metric	-
Lifetime L70B50 (h)	30000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	-

Specific precautions N/A

Spectral power distribution