

## Product information sheet

### 500/PAR56/QWFL GX16d 120V 500W Halogen

Bailey nr.: 142716

EAN-code: 8714681427163

#### Type of light source

Lighting technology used	Halogen
Cap type	GX16d
Non-directional or directional	DLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	Yes

#### Specifications

Energy consumption in on-mode (KWh/1000h)	500
Energy Efficiency Class	G
Useful luminous flux (use) in lm	8000
Beam angle correspondence	Narrow cone (90°)
Correlated colour temperature (K)	3000
On-mode power (Pon) in W	500,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	100
Outer dimension (Height) in mm	127
Outer dimensions (Width) in mm	178
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	-
Chromaticity coordinate (y)	-
Peak luminous intensity (cd)	16875
Beam angle (°)	(40×24)±4/50%
R9 Colour rendering index	-
Survival factor	N/A
Lumen maintenance factor	N/A
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	2000
Nominal voltage (V)	120
Voltage type	-
Frequency	-



Specific precautions

Lights source for transport signalling purposes. Not intended for use in other applications. Use in fixture rated for this product.

Spectral power distribution