

Product information sheet

LED Floodlight RGBW Basic 50W Remote Control

Bailey nr.: 143756

EAN-code: 8714681437568

Type of light source

Lighting technology used	LED
Cap type	-
Non-directional or directional	DLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	Yes



Specifications

Energy consumption in on-mode (KWh/1000h)	50
Energy Efficiency Class	G
Useful luminous flux (use) in lm	1600
Beam angle correspondence	Wide cone (120°)
Correlated colour temperature (K)	RGBW
On-mode power (Pon) in W	50,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	70
Outer dimension (Height) in mm	215
Outer dimensions (Width) in mm	195
Outer dimensions (Depth) in mm	23
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,228
Chromaticity coordinate (y)	0,139
Peak luminous intensity (cd)	-
Beam angle (°)	120
R9 Colour rendering index	0
Survival factor	0,90
Lumen maintenance factor	0,80
Displacement factor	0,90
Colour consistency in McAdam ellipses	-
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	1,0
Stroboscopic effect metric	-
Lifetime L70B50 (h)	25000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	50/60

Specific precautions N/A

Spectral power distribution