

Product information sheet

Pendant 1M LED FIL G125 2200K Battery

Bailey nr.: 144688

EAN-code: 8714681446881

Type of light source

Lighting technology used	LED
Cap type	E27
Non-directional or directional	NDLS
Mains or non-mains	Battery
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	Yes



Specifications

Energy consumption in on-mode (KWh/1000h)	1
Energy Efficiency Class	N/A
Useful luminous flux (use) in lm	50
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	2200
On-mode power (Pon) in W	1,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	176
Outer dimensions (Width) in mm	125
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	-
Chromaticity coordinate (y)	-
Peak luminous intensity (cd)	N/A
Beam angle (°)	N/A
R9 Colour rendering index	-
Survival factor	-
Lumen maintenance factor	-
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	N/A
Nominal voltage (V)	3
Voltage type	-
Frequency	-

Specific precautions N/A

Spectral power distribution