

Product information sheet

AR48 GY4 24V 20W 8D ALU 4000h 41930SP

Bailey nr.: 20400040207

EAN-code: 8714681402078

Type of light source

Lighting technology used	Halogen
Cap type	GY4
Non-directional or directional	DLS
Mains or non-mains	NMLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	Yes
Dimmable	Yes

Specifications

Energy consumption in on-mode (KWh/1000h)	20
Energy Efficiency Class	G
Useful luminous flux (use) in lm	140
Beam angle correspondence	Narrow cone (90°)
Correlated colour temperature (K)	2900
On-mode power (Pon) in W	20,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	100
Outer dimension (Height) in mm	36
Outer dimensions (Width) in mm	48
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,440
Chromaticity coordinate (y)	0,403
Peak luminous intensity (cd)	100
Beam angle (°)	8
R9 Colour rendering index	98
Survival factor	N/A
Lumen maintenance factor	N/A
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	4000
Nominal voltage (V)	24
Voltage type	AC/DC
Frequency	-



Specific precautions

Light source for use in high temperature ?300°C ovens. Not intended for use in other applications.

Spectral power distribution

