

## Product information sheet

### EcoPack LED Party G45 B22d 1W Red Bulk

Bailey nr.: 80100029723

EAN-code: 8714681297230

#### Type of light source

|                                |      |
|--------------------------------|------|
| Lighting technology used       | LED  |
| Cap type                       | B22d |
| Non-directional or directional | NDLS |
| Mains or non-mains             | MLS  |
| Connected light source (CLS)   | No   |
| Colour-tuneable light source   | No   |
| Envelope                       | No   |
| High luminance light source    | No   |
| Anti-glare shield              | No   |
| Dimmable                       | No   |



#### Specifications

|   |               |
|---|---------------|
| Energy consumption in on-mode (KWh/1000h)   | 1             |
| Energy Efficiency Class                     | G             |
| Useful luminous flux (use) in lm            | 7             |
| Beam angle correspondence                   | Sphere (360°) |
| Correlated colour temperature (K)           | Red           |
| On-mode power (Pon) in W                    | 1,0           |
| Standby power (Psb) in W                    | 0,00          |
| Networked standby power for CLS (Pnet) in W | -             |
| Colour rendering index                      | 70            |
| Outer dimension (Height) in mm              | 70            |
| Outer dimensions (Width) in mm              | 45            |
| Outer dimensions (Depth) in mm              | -             |
| Claim of equivalent power                   | No            |
| Equivalent power (W)                        | -             |
| Chromaticity coordinate (x)                 | 0,704         |
| Chromaticity coordinate (y)                 | 0,295         |
| Peak luminous intensity (cd)                | N/A           |
| Beam angle (°)                              | N/A           |
| R9 Colour rendering index                   | 0             |
| Survival factor                             | 0,90          |
| Lumen maintenance factor                    | 0,96          |
| Displacement factor                         | 0,11          |
| Colour consistency in McAdam ellipses       | -             |
| Claim CFL-ni                                | No            |
| Replacement claim (W)                       | -             |
| Flicker metric                              | 1,0           |
| Stroboscopic effect metric                  | 0,4           |
| Lifetime L70B50 (h)                         | 20000         |
| Nominal voltage (V)                         | 220-240       |
| Voltage type                                | AC            |
| Frequency                                   | 50/60         |

Specific precautions N/A

Spectral power distribution