

Product information sheet

LED PL G24q TC-DEL 6W 830 CL

Bailey nr.: 80100035510

EAN-code: 8714681355107

Type of light source

Lighting technology used	LED
Cap type	G24q
Non-directional or directional	DLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



Specifications

Energy consumption in on-mode (KWh/1000h)	6
Energy Efficiency Class	G
Useful luminous flux (use) in lm	420
Beam angle correspondence	Wide cone (120°)
Correlated colour temperature (K)	3000
On-mode power (Pon) in W	6,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	136
Outer dimensions (Width) in mm	46
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	-
Chromaticity coordinate (y)	-
Peak luminous intensity (cd)	-
Beam angle (°)	120
R9 Colour rendering index	-
Survival factor	-
Lumen maintenance factor	-
Displacement factor	-
Colour consistency in McAdam ellipses	-
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	-
Stroboscopic effect metric	-
Lifetime L70B50 (h)	50000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	-

Specific precautions

Disconnect ballast before use. Connect directly to the mains voltage (AC).

Spectral power distribution