

Product information sheet

LED FIL T25X95 E14 1.5W (16W) 150lm 827 Clear

Bailey nr.: 80100035632


EAN-code: 8714681356326

Type of light source

Lighting technology used	LED
Cap type	E14
Non-directional or directional	NDLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No

Specifications

Energy consumption in on-mode (KWh/1000h)	2
Energy Efficiency Class	F
Useful luminous flux (use) in lm	150
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	2700
On-mode power (Pon) in W	1,5
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	95
Outer dimensions (Width) in mm	25
Outer dimensions (Depth) in mm	-
Claim of equivalent power	Yes
Equivalent power (W)	16
Chromaticity coordinate (x)	0,495
Chromaticity coordinate (y)	0,402
Peak luminous intensity (cd)	N/A
Beam angle (°)	320
R9 Colour rendering index	57
Survival factor	0,99
Lumen maintenance factor	0,96
Displacement factor	0,80
Colour consistency in McAdam ellipses	5
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	0,3
Stroboscopic effect metric	0,4
Lifetime L70B50 (h)	15000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	50/60



Specific precautions

N/A

Spectral power distribution

