

Product information sheet

LED27 Ba15d 10-30V DC 3.2W DL

Bailey nr.: 80100036370

EAN-code: 8714681363706

Type of light source

Lighting technology used	LED
Cap type	Bay15d
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



Specifications

Energy consumption in on-mode (KWh/1000h)	4
Energy Efficiency Class	G
Useful luminous flux (use) in lm	266
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	6000
On-mode power (Pon) in W	3,2
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	55
Outer dimensions (Width) in mm	22
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	-
Chromaticity coordinate (y)	-
Peak luminous intensity (cd)	N/A
Beam angle (°)	N/A
R9 Colour rendering index	-
Survival factor	-
Lumen maintenance factor	-
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	20000
Nominal voltage (V)	10-30
Voltage type	DC
Frequency	-

Specific precautions

Lights source for signalling purposes. Not intended for use in other applications.

Spectral power distribution