

## Product information sheet

### LED FIL G4 12V 2W 160lm 927 Clear

Bailey nr.: 80100038379

EAN-code: 8714681383797

#### Type of light source

Lighting technology used	LED
Cap type	G4
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



#### Specifications

Energy consumption in on-mode (KWh/1000h)	2
Energy Efficiency Class	G
Useful luminous flux (use) in lm	160
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	2700
On-mode power (Pon) in W	2,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	90
Outer dimension (Height) in mm	45
Outer dimensions (Width) in mm	16
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,455
Chromaticity coordinate (y)	0,412
Peak luminous intensity (cd)	N/A
Beam angle (°)	280
R9 Colour rendering index	45
Survival factor	1,00
Lumen maintenance factor	0,93
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	15000
Nominal voltage (V)	12
Voltage type	AC/DC
Frequency	50/60

Specific precautions

N/A

Spectral power distribution

