

Product information sheet

LED FIL G9 DIM 2.4W (21W) 200lm 927 Clear

Bailey nr.: 80100038384


EAN-code: 8714681383841

Type of light source

Lighting technology used	LED
Cap type	G9
Non-directional or directional	NDLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	Yes

Specifications

Energy consumption in on-mode (KWh/1000h)	3
Energy Efficiency Class	G
Useful luminous flux (use) in lm	200
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	2700
On-mode power (Pon) in W	2,4
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	90
Outer dimension (Height) in mm	68
Outer dimensions (Width) in mm	11
Outer dimensions (Depth) in mm	-
Claim of equivalent power	Yes
Equivalent power (W)	21
Chromaticity coordinate (x)	0,458
Chromaticity coordinate (y)	0,411
Peak luminous intensity (cd)	N/A
Beam angle (°)	280
R9 Colour rendering index	54
Survival factor	1,00
Lumen maintenance factor	0,93
Displacement factor	0,80
Colour consistency in McAdam ellipses	5
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	0,7
Stroboscopic effect metric	0,4
Lifetime L70B50 (h)	15000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	50/60



Specific precautions

N/A

Spectral power distribution

