

Product information sheet

LED C6 E10 10V-55V 0.3W 6lm 820 RI Clear

Bailey nr.: 80100038773

EAN-code: 8714681387733

Type of light source

Lighting technology used	LED
Cap type	E10
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



Specifications

Energy consumption in on-mode (KWh/1000h)	1
Energy Efficiency Class	G
Useful luminous flux (use) in lm	6
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	2000
On-mode power (Pon) in W	0,3
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	45
Outer dimensions (Width) in mm	14
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,524
Chromaticity coordinate (y)	0,435
Peak luminous intensity (cd)	N/A
Beam angle (°)	360
R9 Colour rendering index	-
Survival factor	-
Lumen maintenance factor	-
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	15000
Nominal voltage (V)	10-55
Voltage type	AC
Frequency	-

Specific precautions N/A

Spectral power distribution