

## Product information sheet

### Spiraled Leslie G125 E27 4W 100lm 922 Metal DIM

Bailey nr.: 80100039076

EAN-code: 8714681390764

#### Type of light source

Lighting technology used	LED
Cap type	E27
Non-directional or directional	NDLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	Yes



#### Specifications

Energy consumption in on-mode (KWh/1000h)	4
Energy Efficiency Class	G
Useful luminous flux (use) in lm	100
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	2200
On-mode power (Pon) in W	4,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	90
Outer dimension (Height) in mm	160
Outer dimensions (Width) in mm	125
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,523
Chromaticity coordinate (y)	0,415
Peak luminous intensity (cd)	N/A
Beam angle (°)	280
R9 Colour rendering index	75
Survival factor	-
Lumen maintenance factor	-
Displacement factor	-
Colour consistency in McAdam ellipses	6
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	-
Stroboscopic effect metric	-
Lifetime L70B50 (h)	15000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	-

Specific precautions N/A

Spectral power distribution