

Product information sheet


LED FIL WarmDim G125 E27 6W (50W) 640lm 919-927 Clear

Bailey nr.: 80100040293

EAN-code: 8714681402931

Type of light source	
Lighting technology used	LED
Cap type	E27
Non-directional or directional	NDLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	Yes






Bailey
80100040293

A	▶
B	▶
C	▶
D	▶
E	▶
F	▶
G	▶

◀ F

6
kWh/1000h



2019/2015

Specifications	
Energy consumption in on-mode (KWh/1000h)	6
Energy Efficiency Class	F
Useful luminous flux (use) in lm	640
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	2700
On-mode power (Pon) in W	6,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	90
Outer dimension (Height) in mm	160
Outer dimensions (Width) in mm	125
Outer dimensions (Depth) in mm	-
Claim of equivalent power	Yes
Equivalent power (W)	50
Chromaticity coordinate (x)	0,459
Chromaticity coordinate (y)	0,408
Peak luminous intensity (cd)	N/A
Beam angle (°)	280
R9 Colour rendering index	58
Survival factor	1,00
Lumen maintenance factor	0,93
Displacement factor	0,80
Colour consistency in McAdam ellipses	5
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	0,8
Stroboscopic effect metric	0,4
Lifetime L70B50 (h)	15000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	50/60

Specific precautions N/A

Spectral power distribution

