

## Product information sheet

### LED R7s Slim 12X78 5W 390lm 830

Bailey nr.: 80100040400

EAN-code: 8714681404003

#### Type of light source

Lighting technology used	LED
Cap type	R7s
Non-directional or directional	NDLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



**ENERGY**

**Bailey**  
80100040400

A  
B  
C  
D  
E  
F  
G

**5**  
kWh/1000h

2019/2015

#### Specifications

Energy consumption in on-mode (KWh/1000h)	5
Energy Efficiency Class	G
Useful luminous flux (use) in lm	390
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	3000
On-mode power (Pon) in W	5,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	78
Outer dimensions (Width) in mm	12
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,450
Chromaticity coordinate (y)	0,413
Peak luminous intensity (cd)	N/A
Beam angle (°)	360
R9 Colour rendering index	80
Survival factor	0,97
Lumen maintenance factor	0,96
Displacement factor	0,80
Colour consistency in McAdam ellipses	6
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	0,3
Stroboscopic effect metric	0,6
Lifetime L70B50 (h)	25000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	50/60

Specific precautions

N/A

Spectral power distribution

