

## Product information sheet

### LED Ecobasic Compact T37 E27 5W 450lm 840

Bailey nr.: 80100040591

EAN-code: 8714681405918

#### Type of light source

|                                |      |
|--------------------------------|------|
| Lighting technology used       | LED  |
| Cap type                       | E27  |
| Non-directional or directional | NDLS |
| Mains or non-mains             | MLS  |
| Connected light source (CLS)   | No   |
| Colour-tuneable light source   | No   |
| Envelope                       | No   |
| High luminance light source    | No   |
| Anti-glare shield              | No   |
| Dimmable                       | No   |



**ENERGY**

**Bailey**  
80100040591

A  
B  
C  
D  
E  
**F**  
G

**5**  
kWh/1000h

2019/2015

#### Specifications

|   |               |
|---|---------------|
| Energy consumption in on-mode (KWh/1000h)   | 5             |
| Energy Efficiency Class                     | F             |
| Useful luminous flux (use) in lm            | 450           |
| Beam angle correspondence                   | Sphere (360°) |
| Correlated colour temperature (K)           | 4000          |
| On-mode power (Pon) in W                    | 5,0           |
| Standby power (Psb) in W                    | 0,00          |
| Networked standby power for CLS (Pnet) in W | -             |
| Colour rendering index                      | 80            |
| Outer dimension (Height) in mm              | 116           |
| Outer dimensions (Width) in mm              | 37            |
| Outer dimensions (Depth) in mm              | -             |
| Claim of equivalent power                   | No            |
| Equivalent power (W)                        | -             |
| Chromaticity coordinate (x)                 | 0,388         |
| Chromaticity coordinate (y)                 | 0,387         |
| Peak luminous intensity (cd)                | N/A           |
| Beam angle (°)                              | 180           |
| R9 Colour rendering index                   | 0             |
| Survival factor                             | 0,90          |
| Lumen maintenance factor                    | 0,96          |
| Displacement factor                         | 0,50          |
| Colour consistency in McAdam ellipses       | 6             |
| Claim CFL-ni                                | No            |
| Replacement claim (W)                       | -             |
| Flicker metric                              | 1,0           |
| Stroboscopic effect metric                  | 0,4           |
| Lifetime L70B50 (h)                         | 15000         |
| Nominal voltage (V)                         | 220-240       |
| Voltage type                                | AC            |
| Frequency                                   | 50/60         |

Specific precautions

N/A

Spectral power distribution

