

Product information sheet


LED G4 12V-24V 1W 110lm 830 Clear

Bailey nr.: 80100040989

EAN-code: 8714681409893

Type of light source

Lighting technology used	LED
Cap type	G4
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



Specifications

Energy consumption in on-mode (KWh/1000h)	1
Energy Efficiency Class	F
Useful luminous flux (use) in lm	110
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	3000
On-mode power (Pon) in W	1,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	36
Outer dimensions (Width) in mm	10
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,447
Chromaticity coordinate (y)	0,410
Peak luminous intensity (cd)	N/A
Beam angle (°)	300
R9 Colour rendering index	8
Survival factor	0,90
Lumen maintenance factor	0,96
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	25000
Nominal voltage (V)	12-24
Voltage type	AC/DC
Frequency	-

Specific precautions

N/A

Spectral power distribution

