

Product information sheet

LED Ba15d T15X45 12V AC/DC 1.8W WW

Bailey nr.: 80100041230

EAN-code: 8714681412305

Type of light source

Lighting technology used	LED
Cap type	Ba15d
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



Specifications

Energy consumption in on-mode (KWh/1000h)	2
Energy Efficiency Class	G
Useful luminous flux (use) in lm	150
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	3000
On-mode power (Pon) in W	1,8
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	45
Outer dimensions (Width) in mm	15
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,440
Chromaticity coordinate (y)	0,403
Peak luminous intensity (cd)	N/A
Beam angle (°)	N/A
R9 Colour rendering index	13
Survival factor	0,90
Lumen maintenance factor	0,92
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	20000
Nominal voltage (V)	12
Voltage type	-
Frequency	-

Specific precautions

Lights source for signalling purposes. Not intended for use in other applications.

Spectral power distribution