

Product information sheet

LED Flicker Flame C37 E14 1W 50lm 1800K

Bailey nr.: 80100041288

EAN-code: 8714681412886

Type of light source

Lighting technology used	LED
Cap type	E14
Non-directional or directional	NDLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



Specifications

Energy consumption in on-mode (KWh/1000h)	1
Energy Efficiency Class	G
Useful luminous flux (use) in lm	50
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	1800
On-mode power (Pon) in W	1,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	59
Outer dimension (Height) in mm	126
Outer dimensions (Width) in mm	37
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	0,584
Chromaticity coordinate (y)	0,403
Peak luminous intensity (cd)	N/A
Beam angle (°)	N/A
R9 Colour rendering index	-
Survival factor	-
Lumen maintenance factor	-
Displacement factor	0,40
Colour consistency in McAdam ellipses	-
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	-
Stroboscopic effect metric	-
Lifetime L70B50 (h)	30000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	-

Specific precautions N/A

Spectral power distribution