

## Product information sheet

### LED Ecobasic PAR16 GU10 DIM 5.5W (50W) 450lm 830 38D

Bailey nr.: 80100041661


EAN-code: 8714681416617

#### Type of light source

Lighting technology used	LED
Cap type	GU10
Non-directional or directional	DLS
Mains or non-mains	MLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	Yes

#### Specifications

Energy consumption in on-mode (KWh/1000h)	6
Energy Efficiency Class	F
Useful luminous flux (use) in lm	450
Beam angle correspondence	Narrow cone (90°)
Correlated colour temperature (K)	3000
On-mode power (Pon) in W	5,5
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	60
Outer dimensions (Width) in mm	50
Outer dimensions (Depth) in mm	-
Claim of equivalent power	Yes
Equivalent power (W)	50
Chromaticity coordinate (x)	0,440
Chromaticity coordinate (y)	0,403
Peak luminous intensity (cd)	850
Beam angle (°)	38
R9 Colour rendering index	2
Survival factor	0,90
Lumen maintenance factor	0,96
Displacement factor	0,50
Colour consistency in McAdam ellipses	5
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	1,0
Stroboscopic effect metric	0,4
Lifetime L70B50 (h)	25000
Nominal voltage (V)	220-240
Voltage type	AC
Frequency	50/60



Specific precautions

N/A

Spectral power distribution

