

## Product information sheet

### E14 C35 130V 60W Clear

Bailey nr.: CE498130060

EAN-code: 8714681021422

#### Type of light source

|                                |              |
|--------------------------------|--------------|
| Lighting technology used       | Incandescent |
| Cap type                       | E14          |
| Non-directional or directional | NDLS         |
| Mains or non-mains             | MLS          |
| Connected light source (CLS)   | No           |
| Colour-tuneable light source   | No           |
| Envelope                       | No           |
| High luminance light source    | No           |
| Anti-glare shield              | No           |
| Dimmable                       | Yes          |



#### Specifications

|                                             |               |
|---------------------------------------------|---------------|
| Energy consumption in on-mode (KWh/1000h)   | 60            |
| Energy Efficiency Class                     | G             |
| Useful luminous flux (use) in lm            | 570           |
| Beam angle correspondence                   | Sphere (360°) |
| Correlated colour temperature (K)           | 2700          |
| On-mode power (Pon) in W                    | 60,0          |
| Standby power (Psb) in W                    | 0,00          |
| Networked standby power for CLS (Pnet) in W | -             |
| Colour rendering index                      | 100           |
| Outer dimension (Height) in mm              | 100           |
| Outer dimensions (Width) in mm              | 35            |
| Outer dimensions (Depth) in mm              | -             |
| Claim of equivalent power                   | No            |
| Equivalent power (W)                        | -             |
| Chromaticity coordinate (x)                 | -             |
| Chromaticity coordinate (y)                 | -             |
| Peak luminous intensity (cd)                | N/A           |
| Beam angle (°)                              | N/A           |
| R9 Colour rendering index                   | -             |
| Survival factor                             | N/A           |
| Lumen maintenance factor                    | N/A           |
| Displacement factor                         | N/A           |
| Colour consistency in McAdam ellipses       | N/A           |
| Claim CFL-ni                                | No            |
| Replacement claim (W)                       | -             |
| Flicker metric                              | N/A           |
| Stroboscopic effect metric                  | N/A           |
| Lifetime L70B50 (h)                         | 1000          |
| Nominal voltage (V)                         | 110-130       |
| Voltage type                                | AC            |
| Frequency                                   | -             |

Specific precautions

N/A

Spectral power distribution