

## Product information sheet

### E14 C35 240V 40W Yellow

Bailey nr.: CE498240040Y

EAN-code: 8714681237786

#### Type of light source

|                                |              |
|--------------------------------|--------------|
| Lighting technology used       | Incandescent |
| Cap type                       | E14          |
| Non-directional or directional | NDLS         |
| Mains or non-mains             | MLS          |
| Connected light source (CLS)   | No           |
| Colour-tuneable light source   | No           |
| Envelope                       | No           |
| High luminance light source    | No           |
| Anti-glare shield              | No           |
| Dimmable                       | Yes          |



#### Specifications

|   |         |
|---|---------|
| Energy consumption in on-mode (KWh/1000h)   | 40      |
| Energy Efficiency Class                     | N/A     |
| Useful luminous flux (use) in lm            | -       |
| Beam angle correspondence                   | -       |
| Correlated colour temperature (K)           | Yellow  |
| On-mode power (Pon) in W                    | 40,0    |
| Standby power (Psb) in W                    | 0,00    |
| Networked standby power for CLS (Pnet) in W | -       |
| Colour rendering index                      | 100     |
| Outer dimension (Height) in mm              | 100     |
| Outer dimensions (Width) in mm              | 35      |
| Outer dimensions (Depth) in mm              | -       |
| Claim of equivalent power                   | No      |
| Equivalent power (W)                        | -       |
| Chromaticity coordinate (x)                 | -       |
| Chromaticity coordinate (y)                 | -       |
| Peak luminous intensity (cd)                | N/A     |
| Beam angle (°)                              | N/A     |
| R9 Colour rendering index                   | -       |
| Survival factor                             | N/A     |
| Lumen maintenance factor                    | N/A     |
| Displacement factor                         | N/A     |
| Colour consistency in McAdam ellipses       | N/A     |
| Claim CFL-ni                                | No      |
| Replacement claim (W)                       | -       |
| Flicker metric                              | N/A     |
| Stroboscopic effect metric                  | N/A     |
| Lifetime L70B50 (h)                         | 1000    |
| Nominal voltage (V)                         | 220-240 |
| Voltage type                                | AC      |
| Frequency                                   | -       |

Specific precautions N/A

Spectral power distribution