

Product information sheet

T5 4W 16X136 Daylight

Bailey nr.: FT004DL

EAN-code: 8714681040034

Type of light source

| | |
|--------------------------------|-------------|
| Lighting technology used | Fluorescent |
| Cap type | G5 |
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Connected light source (CLS) | No |
| Colour-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Dimmable | No |



Specifications

| | |
|---|---------------|
| Energy consumption in on-mode (KWh/1000h) | 4 |
| Energy Efficiency Class | G |
| Useful luminous flux (use) in lm | 115 |
| Beam angle correspondence | Sphere (360°) |
| Correlated colour temperature (K) | 6500 |
| On-mode power (Pon) in W | 4,0 |
| Standby power (Psb) in W | 0,00 |
| Networked standby power for CLS (Pnet) in W | - |
| Colour rendering index | 70 |
| Outer dimension (Height) in mm | 136 |
| Outer dimensions (Width) in mm | 16 |
| Outer dimensions (Depth) in mm | - |
| Claim of equivalent power | No |
| Equivalent power (W) | - |
| Chromaticity coordinate (x) | 0,313 |
| Chromaticity coordinate (y) | 0,337 |
| Peak luminous intensity (cd) | N/A |
| Beam angle (°) | 360 |
| R9 Colour rendering index | 0 |
| Survival factor | N/A |
| Lumen maintenance factor | N/A |
| Displacement factor | N/A |
| Colour consistency in McAdam ellipses | N/A |
| Claim CFL-ni | No |
| Replacement claim (W) | - |
| Flicker metric | N/A |
| Stroboscopic effect metric | N/A |
| Lifetime L70B50 (h) | 6000 |
| Nominal voltage (V) | - |
| Voltage type | - |
| Frequency | - |

Specific precautions N/A

Spectral power distribution