

## Product information sheet

### GY10q-4 4 Pin 27W FPL27EX-N

Bailey nr.: FTC27FPLEXN/50

EAN-code: 4902901125379

#### Type of light source

|                                |         |
|--------------------------------|---------|
| Lighting technology used       | CFLni   |
| Cap type                       | GY10q-3 |
| Non-directional or directional | NDLS    |
| Mains or non-mains             | NMLS    |
| Connected light source (CLS)   | No      |
| Colour-tuneable light source   | No      |
| Envelope                       | No      |
| High luminance light source    | No      |
| Anti-glare shield              | No      |
| Dimmable                       | No      |



#### Specifications

|   |               |
|---|---------------|
| Energy consumption in on-mode (KWh/1000h)   | 27            |
| Energy Efficiency Class                     | G             |
| Useful luminous flux (use) in lm            | 1800          |
| Beam angle correspondence                   | Sphere (360°) |
| Correlated colour temperature (K)           | 5000          |
| On-mode power (Pon) in W                    | 27,0          |
| Standby power (Psb) in W                    | 0,00          |
| Networked standby power for CLS (Pnet) in W | -             |
| Colour rendering index                      | 70            |
| Outer dimension (Height) in mm              | 245           |
| Outer dimensions (Width) in mm              | 20            |
| Outer dimensions (Depth) in mm              | -             |
| Claim of equivalent power                   | No            |
| Equivalent power (W)                        | -             |
| Chromaticity coordinate (x)                 | -             |
| Chromaticity coordinate (y)                 | -             |
| Peak luminous intensity (cd)                | N/A           |
| Beam angle (°)                              | N/A           |
| R9 Colour rendering index                   | -             |
| Survival factor                             | N/A           |
| Lumen maintenance factor                    | N/A           |
| Displacement factor                         | N/A           |
| Colour consistency in McAdam ellipses       | N/A           |
| Claim CFL-ni                                | No            |
| Replacement claim (W)                       | -             |
| Flicker metric                              | N/A           |
| Stroboscopic effect metric                  | N/A           |
| Lifetime L70B50 (h)                         | 8000          |
| Nominal voltage (V)                         | -             |
| Voltage type                                | -             |
| Frequency                                   | -             |

Specific precautions N/A

Spectral power distribution