

Product information sheet

T4 6W/842 12X218 excl. pins Cool White

Bailey nr.: FTR06W842

EAN-code: 8714681296578

Type of light source

Lighting technology used	Fluorescent
Cap type	G5
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



Specifications

Energy consumption in on-mode (KWh/1000h)	6
Energy Efficiency Class	G
Useful luminous flux (use) in lm	360
Beam angle correspondence	Sphere (360°)
Correlated colour temperature (K)	4200
On-mode power (Pon) in W	6,0
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	80
Outer dimension (Height) in mm	218
Outer dimensions (Width) in mm	12
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	-
Chromaticity coordinate (y)	-
Peak luminous intensity (cd)	N/A
Beam angle (°)	N/A
R9 Colour rendering index	-
Survival factor	N/A
Lumen maintenance factor	N/A
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	5000
Nominal voltage (V)	-
Voltage type	-
Frequency	-

Specific precautions N/A

Spectral power distribution