

Product information sheet

PAR36 Screw T. 4.7V 0.5A 4546 Hand Lantern

Bailey nr.: RP36S4546

EAN-code: 8714681135402

Type of light source

Lighting technology used	Incandescent
Cap type	Screw Terminal
Non-directional or directional	DLS
Mains or non-mains	NMLS
Connected light source (CLS)	No
Colour-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Dimmable	No



Specifications

Energy consumption in on-mode (KWh/1000h)	3
Energy Efficiency Class	G
Useful luminous flux (use) in lm	7
Beam angle correspondence	Narrow cone (90°)
Correlated colour temperature (K)	2400
On-mode power (Pon) in W	2,5
Standby power (Psb) in W	0,00
Networked standby power for CLS (Pnet) in W	-
Colour rendering index	100
Outer dimension (Height) in mm	60
Outer dimensions (Width) in mm	112
Outer dimensions (Depth) in mm	-
Claim of equivalent power	No
Equivalent power (W)	-
Chromaticity coordinate (x)	-
Chromaticity coordinate (y)	-
Peak luminous intensity (cd)	600
Beam angle (°)	7
R9 Colour rendering index	-
Survival factor	N/A
Lumen maintenance factor	N/A
Displacement factor	N/A
Colour consistency in McAdam ellipses	N/A
Claim CFL-ni	No
Replacement claim (W)	-
Flicker metric	N/A
Stroboscopic effect metric	N/A
Lifetime L70B50 (h)	100
Nominal voltage (V)	5
Voltage type	AC/DC
Frequency	-

Specific precautions N/A

Spectral power distribution