

Product information sheet

Pigmy E27 30X60 240V 25W Clear Appl.

Bailey nr.: SE760240025

EAN-code: 8714681145449

Type of light source

| | |
|--------------------------------|--------------|
| Lighting technology used | Incandescent |
| Cap type | E27 |
| Non-directional or directional | NDLS |
| Mains or non-mains | MLS |
| Connected light source (CLS) | No |
| Colour-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Dimmable | Yes |



Specifications

| | |
|---|---------------|
| Energy consumption in on-mode (KWh/1000h) | 25 |
| Energy Efficiency Class | G |
| Useful luminous flux (use) in lm | 180 |
| Beam angle correspondence | Sphere (360°) |
| Correlated colour temperature (K) | 2700 |
| On-mode power (Pon) in W | 25,0 |
| Standby power (Psb) in W | 0,00 |
| Networked standby power for CLS (Pnet) in W | - |
| Colour rendering index | 100 |
| Outer dimension (Height) in mm | 60 |
| Outer dimensions (Width) in mm | 30 |
| Outer dimensions (Depth) in mm | - |
| Claim of equivalent power | No |
| Equivalent power (W) | - |
| Chromaticity coordinate (x) | - |
| Chromaticity coordinate (y) | - |
| Peak luminous intensity (cd) | N/A |
| Beam angle (°) | N/A |
| R9 Colour rendering index | - |
| Survival factor | N/A |
| Lumen maintenance factor | N/A |
| Displacement factor | N/A |
| Colour consistency in McAdam ellipses | N/A |
| Claim CFL-ni | No |
| Replacement claim (W) | - |
| Flicker metric | N/A |
| Stroboscopic effect metric | N/A |
| Lifetime L70B50 (h) | 1000 |
| Nominal voltage (V) | 220-240 |
| Voltage type | AC |
| Frequency | - |

Specific precautions N/A

Spectral power distribution