

64259 20 W 12 V

Low-voltage halogen lamps without reflector

Areas of application

- Lamps for special luminaires
- Medical fiber optics (HLX)



Product family benefits

- Compared to standard lamps up to 10 % higher luminous efficacy (HLX)
- Instant light (HLX)

Product family features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)
- HLX tungsten halogen low-voltage lamp with or without reflector
- Dimmable (HLX)





Product datasheet

Technical data


Product information

Order reference	64259 20W 12V G
-----------------	-----------------

Electrical data

Nominal voltage	12.0 V
Nominal wattage	20.00 W

Dimensions & weight



Diameter	9.5 mm
Length	30.0 mm
Light center length (LCL)	19.5 mm ¹⁾
Filament length	1.90 mm
Illuminated field	1.9*2.0 mm ²
Filament diameter	2.0 mm

^{1) ±0.3} mm

Lifespan

Lifespan	1500 h

Additional product data

Base (standard designation)	G4
Minimum diameter of lamp enclosure	9 mm

Capabilities

Burning position	s90
Application	Other


Product datasheet

Certificates & standards

EEI – Energy Label	В
Country specific categorizations	

Order reference	64259 20W 12V G

Product datasheet



Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321352569	64259 20 W 12 V	Folding carton box 1	25 mm x 23 mm x 70 mm	0.04 dm ³	3.00 g
4008321352576	64259 20 W 12 V	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm ³	161.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.