

64626 HLX

Low-voltage halogen lamps without reflector



Areas of application

- Lamps for special luminaires
- Medical fiber optics (HLX)

Product family benefits

- Compared to standard lamps up to 10 % higher luminous efficacy (HLX)
- Instant light (HLX)

Product family features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)
- HLX tungsten halogen low-voltage lamp with or without reflector
- Dimmable (HLX)





Product datasheet

Technical data

Product information

Order reference	64626 HLX
-----------------	-----------


Electrical data

Nominal voltage	12.0 V		
Nominal wattage	100.00 W		

Photometrical data

Color temperature	3450 K
Nominal luminous flux	3500 lm
Color rendering index Ra	100

Dimensions & weight



Diameter	11.5 mm
Length	48.0 mm
Light center length (LCL)	18.0 mm
Filament length	4.20 mm
Illuminated field	4.2*2.3 mm²
Filament diameter	2.3 mm

Lifespan

Lifespan	50 h

Additional product data

Base (standard designation)	PG22	
Product remark	Available on request	
Minimum diameter of lamp enclosure	12 mm	

Product datasheet

Capabilities

Burning position	s90
Application	Other

Certificates & standards


Country specific categorizations

ANSI code	ЕНЕ
LIF	A1/45
Order reference	64626 HLX

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300006765	OSRH64626HLX	-	-	-
4050300006765	OSRH64626HLX	-	-	-

Product datasheet



Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300006765	64626 HLX	Folding carton box 1	70 mm x 23 mm x 25 mm	0.04 dm ³	12.00 g
4050300236421	64626 HLX	Shipping carton box 30	158 mm x 81 mm x 131 mm	1.68 dm³	342.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.