64652 HLX

Low-voltage halogen lamps without reflector

Areas of application

- Lamps for special luminaires
- Medical fiber optics (HLX)

Product family benefits

- Compared to standard lamps up to 10 % higher luminous efficacy (HLX)
- Instant light (HLX)

Product family features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)
- HLX tungsten halogen low-voltage lamp with or without reflector
- Dimmable (HLX)

Product datasheet

Technical data

Product information

Order reference	64652 HLX

Electrical data

Nominal voltage	24.0 V
Nominal wattage	250.00 W

Photometrical data

Color temperature	3400 K
Nominal luminous flux	8200 lm
Color rendering index Ra	100

Dimensions & weight

Diameter	11.5 mm
Length	46.0 mm
Light center length (LCL)	31.8 mm
Filament length	2.60 mm
Illuminated field	2.7*5.0 mm²
Filament diameter	5.0 mm

Lifespan

Lifespan	50 h

Additional product data

Base (standard designation)	GX5.3
Minimum diameter of lamp enclosure	11 mm

Capabilities

Burning position	p90/p15
Application	Other

Certificates & standards

EEI – Energy Label	B

Country specific categorizations

Order reference	64652 HLX

—

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899100916	64652 HLX	Folding carton box 1	25 mm x 23 mm x 70 mm	0.04 dm³	4.60 g
4052899100923	64652 HLX	Shipping carton box 40	144 mm x 107 mm x 121 mm	1.86 dm³	225.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.