

Halogen lamps, medium/high voltage, single-ended




Areas of application

- Professional film and TV work

Product family features

- Operation at mains voltage: 120 V | 230 V | 240 V
- Color temperature: 2,900 K | 3,000 K (with longer lifespan)
- Color temperature: 3,200 K (for professional film and TV work)
- Color temperature: 3,400 K (for maximum luminous efficacy)



Product datasheet

Technical data

Product information

Order reference	64662 300W GY9.
-----------------	-----------------


Electrical data

Nominal wattage	300.00 W
Nominal voltage	240 V

Photometrical data

Nominal luminous flux	5000 lm
Color temperature	2900 K
Color rendering index Ra	100

Dimensions & weight



Diameter	17.5 mm
Length	80.0 mm
Illuminated field	9.0*11.0 mm ²
Filament diameter	11.0 mm

Lifespan

Lifespan	2000 h
----------	--------

Additional product data

Base (standard designation)	GY9.5
-----------------------------	-------

Capabilities

Burning position	Any
------------------	-----

Product datasheet

Certificates & standards

EEI – Energy Label	D
--------------------	---

Country specific categorizations

ANSI code	Other
LIF	M/38
Order reference	64662 300W GY9.

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899144248		Folding carton box 1	- x - x -		35.00 g
4052899144255		Shipping carton box 12	180 mm x 140 mm x 127 mm	3.20 dm ³	417.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For further information on pinch technology, please refer to the following brochure:

“A whole lotta shakin’ goin’ on!” New halogen lamps with quartz pinch technology. (122 W 100 DE 08/05)

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
