

LEDDriving PX-5

LED daytime running light for retrofit



LED pixel technology

Dynamic appearance thanks to faceted optic and dotted pixel technology



DRL

LED daytime running light compatible with a wide range of car models and easy to install



5200 K

For drivers who want to increase visibility during the day



Stylish highlights for your car

LEDDriving PX-5 serves as a high performance and energy-efficient daytime running light for retrofitting on your vehicle. With its patterned diode design of five LEDs, the LEDDriving PX-5 gives your vehicle a modern and stylish look. This daytime running light system is compatible with a wide range of vehicle models and is easy to install. The careful design of the LEDDriving system ensures a horizontal tilt of 10 degrees. In addition, the left-hand and right-hand lamps can be switched, thus making installation uncomplicated. Furthermore, the high color temperature of 5,200 Kelvin and long life of up to 5,000 hours provide endless driving pleasure with LEDDriving PX-5. OSRAM provides a 3-year guarantee for this product. Note: LEDDriving PX-5 is certified according to ECE, SAE and CCC regulations (ECE E4 approval; ECE R87 approval).

Product datasheet

Technical data

Product information

Order reference	LEDDR301
-----------------	----------


Electrical data

Nominal voltage	13.2 V
Nominal wattage	12.5 W

Photometrical data

Color temperature	5200 K
Luminous flux	300 lm

Dimensions & weight



Length	160.0 mm
Product weight	552.00 g
Width	30.0 mm
Height	23.0 mm

Lifespan

Guarantee	3 years
-----------	---------

Additional product data

Connector to lamp	Wire Kit
-------------------	----------

Capabilities

Technology	LED
------------	-----

Certificates & standards

Product datasheet

Standards	ECE R87
Approval marks – approval	E4 approval

Country specific categorizations

Order reference	LEDDRL301
-----------------	-----------

Logistical data



Commodity code	851220009000
----------------	--------------

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899170766	LEDriving PX-5	Folding carton box 1	286 mm x 79 mm x 203 mm	4.59 dm ³	762.00 g
4052899170773	LEDriving PX-5	Shipping carton box 5	444 mm x 305 mm x 231 mm	31.28 dm ³	4349.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 User instruction 336028_LED Daytime Running Light Kit LEDDRL301 (User Manual)
 User instruction 501779_LED Daytime Running Light Kit LEDDRL301 CL15 (User Manual)

Legal advice

ECE E4 approval

ECE R87 approval

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Product datasheet



OSRAM