

XBO 2000 W/HS OFR

XBO for cinema projection | Xenon short-arc lamps 450...10,000 W



Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

Product family benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

Product family features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 450...10,000 W
- Very good color rendering index: R_a >








Product datasheet

Technical data

Electrical data

Nominal current	80.0 A
Current control range	5085 A
Nominal wattage	2000.00 W
Nominal voltage	24.0 V

Dimensions & weight



Diameter	60.0 mm
Length	342.0 mm
Length with base excl. base pins/connection	302.00 mm
Light center length (LCL)	145.0 mm ¹⁾
Electrode gap cold	5.0 mm
Product weight	490.00 g
Cable length	300.0 mm

 $^{^{1)}}$ Distance from end of base to tip of electrode (cold)

Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C

Lifespan

|--|

Additional product data

Base anode (standard designation)	SFaX27-9.5
Base cathode (standard designation)	SFa27-7.9
Product remark	H = Suitable for horizontal burning position/S = Short

Product datasheet

Capabilities

Cooling	Forced ¹⁾
Burning position	s30/p30 ²⁾

 $^{^{1)}}$ Vertical and horizontal

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321081360	OSRXBO2000HSOFR	-	-	-

²⁾ For vertical burning position: anode (+) on top

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321081360	XBO 2000 W/HS OFR	Shipping carton box 1	500 mm x 200 mm x 204 mm	20.40 dm³	1247.00 g
4062172030359	XBO 2000 W/HS OFR	Shipping carton box 1	500 mm x 204 mm x 204 mm	20.81 dm³	1286.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.