

## HMI EVENT 575 W

HMI brand EVENT | Metal halide lamps, single-ended



### Areas of application

- Events, trade fairs or exhibitions of cars, boats, industrial plants and motorcycles

### Product family benefits

- Extremely uniform light distribution, reduced color or brightness shifts
- Constant daylight color temperature throughout the entire lamp lifetime
- High light output
- Very good color rendering index of  $R_a > 90$  throughout the whole lamp lifetime
- Minimal light scattering
- Optimized filling



## Product datasheet

### Technical data


#### Electrical data

|                 |          |
|-----------------|----------|
| Nominal wattage | 575.00 W |
| Nominal voltage | 95.0 V   |
| Nominal current | 76.9 A   |

#### Photometrical data

|                       |          |
|-----------------------|----------|
| Nominal luminous flux | 49000 lm |
| Color temperature     | 6000 K   |

#### Dimensions & weight



|          |          |
|----------|----------|
| Diameter | 30.0 mm  |
| Length   | 145.0 mm |

#### Lifespan

|          |        |
|----------|--------|
| Lifespan | 1000 h |
|----------|--------|

#### Additional product data

|                             |     |
|-----------------------------|-----|
| Base (standard designation) | G22 |
|-----------------------------|-----|

#### Capabilities

|                  |       |
|------------------|-------|
| Burning position | Other |
|------------------|-------|

## Product datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Logistical Data

| Product code  | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume               | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4052899301726 | HMI EVENT 575 W     | Folding carton box<br>1      | 46 mm x 46 mm x<br>143 mm            | 0.30 dm <sup>3</sup> | 153.00 g     |
| 4052899301733 | HMI EVENT 575 W     | Shipping carton box<br>10    | 245 mm x 105 mm x<br>165 mm          | 4.24 dm <sup>3</sup> | 1600.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.