

LEDDriving SL P27/7W YELLOW

Ideal replacement for any vehicle




Suitable for various vehicle exterior applications

Available in Amber



Replaces conventional P277W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P27/7W

LEDDriving SL P27/7W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P27/7W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Technical data

Product information

Order reference	3157DYP
Product type (off-road vs. on-road)	Off-road \pm P27/7W
Application (Category and Product specific)	Mainly used for signal/ indicator applications


Electrical data

Power input	1.7 W
Nominal voltage	12.0 V
Nominal wattage	1.90 W
Test voltage	13.5 V
Power input tolerance	\pm 25 %

Photometrical data

Luminous flux	55/10 lm
Luminous flux tolerance	\pm 25 %
Light color LED	Yellow

Dimensions & weight



Diameter	25.7 mm
Product weight	13.30 g
Length	49.0 mm

Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

Product datasheet

Additional product data

Base (standard designation)	W2.5x16q
-----------------------------	----------

Capabilities

Technology	LED ¹⁾
------------	-------------------

¹⁾ Light-emitting diode lamp

Country specific categorizations




Order reference	3157DYP
-----------------	---------

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172151665	LEDiving SL $\hat{=}$ P27/7W	Blister 2	135 mm x 95 mm x 18 mm	0.23 dm ³	39.00 g
4062172151672	LEDiving SL $\hat{=}$ P27/7W	Shipping carton box 10	115 mm x 105 mm x 145 mm	1.75 dm ³	228.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 Brochures LEDiving Retrofits - Exchange overview (EN)
 Brochures 618438_LEDiving RETROFIT application overview (EN)
 360 Degree Image LEDiving SL P277W 3157DYP-02B

Safety advice

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.