OSRAM

LEDriving SL C5W 6413 WHITE

Ideal replacement for any vehicle





Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional C5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for C5W

LEDriving SL C5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional C5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Technical data

Product information

Order reference	6413DWP	
Product type (off-road vs. on-road)	Off-road ≙ C5W	
Application (Category and Product specific)	specific) Mainly used for number plate/ interior applications	


Electrical data

Power input	0.8 W
Nominal voltage	12.0 V
Nominal wattage	0.60 W
Test voltage	13.5 V
Power input tolerance	±25 %

Photometrical data

Luminous flux	45 lm	
Luminous flux tolerance	±30 %	
Color temperature	6000 K	
Light color LED	Cool white	

Dimensions & weight



Diameter	11.0 mm
Product weight	2.90 g
Length	41.0 mm

Lifespan

Lifespan B3	2500 h
Lifespan Tc	5000 h
Guarantee	4 years

Product datasheet

Additional product data

Base (standard designation) SV8.5-8

Capabilities

Technology	LED ¹⁾
------------	-------------------

¹⁾ Light-emitting diode lamp

Country specific categorizations

Order reference	6413DWP
-----------------	---------

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172150675	LEDriving SL ≜ C5W	Blister 1	135 mm x 95 mm x 18 mm	0.23 dm ³	15.15 g
4062172150682	LEDriving SL ≜ C5W	Shipping carton box 5	104 mm x 71 mm x 146 mm	1.08 dm ³	111.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
太	Brochures LEDriving Retrofits - Exchange overview (EN)
太	Brochures 618438_LEDriving RETROFIT application overview (EN)
	360 Degree Image LEDriving SL C5W 6438DWP-01B 6418DWP-01B 6413DWP-01B

Safety advice

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

