
Product datasheet

DULUX L 55 W/840 2G11

OSRAM DULUX L LUMILUX | CFLni, with 4-pin 2G11 base for ECG/CCG operation



Product datasheet

Technical data


Electrical data

Nominal wattage	55.00 W
Rated wattage	55.00 W

Photometrical data

Nominal luminous flux	4800 lm
Light color (designation)	LUMILUX Cool White
Luminous flux at	4800 lm
Rated luminous flux	4800 lm
Rated color temperature	4000 K
Rated LLMF at 4,000 h	0.90
Rated LLMF at 6,000 h	0.88
Rated LLMF at 8,000 h	0.85
Rated LLMF at 12,000 h	0.84
Rated LLMF at 16,000 h	0.81
Rated LLMF at 20,000 h	0.80
Luminance	3.2 cd/cm ²
Color rendering index Ra	≥80
Color temperature	4000 K
Luminous flux	4800 lm
Color rendering index Ra	80...89

Dimensions & weight



Diameter	17.5 mm
Overall length	530.5 mm
Tube diameter	17.5 mm
Length	533.0 mm

Product datasheet

Length acc. to IEC standard	535 mm
Length with base excl. base pins/connection	533.00 mm
Outer bulb	T17,5
Product weight	113.00 g
Maximum diameter	17.0 mm

Temperatures & operating conditions

Rated ambient temp.w.max.luminous flux	25.0 °C
--	---------

Lifespan

Rated lamp life time	20000 h
Service life	13000 h ¹⁾
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000 h	0.81
Rated lamp survival factor at 20,000 h	0.50
Operation mode LLMF/LSF	HF
Lifespan	20000 h ¹⁾
Nominal lamp life time	20000 h

¹⁾ With preheat ECG

Additional product data

Base (standard designation)	2G11
Mercury content	2.5 mg
Appropriate disposal acc. to WEEE	Yes
Product remark	For ECG operation only

Capabilities

Dimmable	Yes
Suitable for indoor	Yes

Certificates & standards

Energy efficiency class	A+
Energy consumption	61 kWh/1000h


Country specific categorizations

Product datasheet


ILCOS	FSDH-55/840-/P/-2G11-43,9/533
Order reference	DULUX L 55W/840

Equipment / Accessories

- Suitable for standard control gears and starters
- Suitable for operation on electronic and conventional control gear



SERIES CONNECTION WITH QUICKTRONIC



SINGLE LAMP WITH QUICKTRONIC

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300295879	DULUX L 55 W/840 2G11	Shipping carton box 10 Pieces Folding carton box	136 mm x 103 mm x 578 mm	8.10 dm ³	1663.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on QUICKTRONIC electronic control gear go to

- ▶ www.osram.com/QUICKTRONIC

For more information on the system guarantee and the terms and conditions of the guarantee visit

- ▶ www.osram.com/system-guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany

DULUX L 55 W/840 2G11

OSRAM DULUX L LUMILUX | CFLni, with 4-pin 2G11 base for ECG/CCG operation

Product name	Product name ECG	EAN	Nominal current	Nominal wattage + Power loss	Power factor λ [PIM]	Luminous flux at 35 °C
DULUX L 55 W/840 2G11	QT-FQ 2x80	4050300825564	0.59 A	122.00 W	0.99	4800 lm
	QTi 1x28/54 DIM	4050300870588	0.26 A	59.00 W	0.99	4800 lm
	QTi 1x35/49/80 GII	4008321383372	0.26 A	59.00 W	0.99	4800 lm
	QTi 2x28/54 DIM	4050300870717	0.51 A	115.00 W	0.99	4800 lm
	QTi 2x35/49/80 GII	4008321658951	0.53 A	119.00 W	0.98	4800 lm
	QTi DALI 1x28/54 DIM	4050300870809	0.26 A	59.00 W	0.99	4800 lm
	QTi DALI 2x28/54 DIM	4050300870502	0.51 A	115.00 W	0.99	4800 lm
	QTP-DL 2x55 GII	4008321390172	0.51 A	116.00 W	0.99	4800 lm
	QTP-FC 1x55	4008321537041	0.26 A	59.00 W	0.98	4800 lm
	QTP-OPTIMAL 1x54-58	4008321873729	0.24 A	50.00 W	0.98	4800 lm
QTP-OPTIMAL 2x54-58	4008321880253	0.48 A	110.00 W	0.99	4800 lm	

Product name	Product name ECG	EAN	Number of lighting outlets
DULUX L 55 W/840 2G11	QT-FQ 2x80	4050300825564	2
	QTi 1x28/54 DIM	4050300870588	1
	QTi 1x35/49/80 GII	4008321383372	1
	QTi 2x28/54 DIM	4050300870717	2

Product datasheet

Product name	Product name ECG	EAN	Number of lighting outlets
	QTi 2x35/49/80 GII	4008321658951	2
	QTi DALI 1x28/54 DIM	4050300870809	1
	QTi DALI 2x28/54 DIM	4050300870502	2
	QTP-DL 2x55 GII	4008321390172	2
	QTP-FC 1x55	4008321537041	1
	QTP-OPTIMAL 1x54-58	4008321873729	1
	QTP-OPTIMAL 2x54-58	4008321880253	2