

SIG 64002

SIRIUS | Low-voltage halogen lamps with dichroic reflector, road traffic



Product datasheet

Technical data

Electrical data

Nominal voltage	12.0 V
Rated wattage	20.00 W
Nominal wattage	20.00 W
Nominal voltage	12 V


Photometrical data

Rated luminous flux	120 lm
Nominal luminous flux	120 lm
Color rendering index Ra	100
Luminous flux	120 lm

Light technical data

Aperture window, maximum	10.2 mm
Starting time	0.0 s

Dimensions & weight



Diameter	51.0 mm
Base diameter	24.5 mm
Overall length	46.5 mm
Product weight	38.00 g
Length	46.5 mm
Outer bulb	T11

Additional product data

Base (standard designation)	K23d
Mercury-free	Yes

Product datasheet


Country specific categorizations

Order reference	SIG 64002 CL 20
------------------------	-----------------

Country specific information

Product code	METEL code	SEG number	STK number	UK Org
4050300246505	OSRSIG64002HC	8334870	4739706	-
4050300246505	OSRSIG64002HC	8334870	4739706	-

Product datasheet



Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300246505	SIG 64002	Folding carton box 1	53 mm x 52 mm x 52 mm	0.14 dm ³	46.60 g
4050300246512	SIG 64002	Shipping carton box 10	301 mm x 63 mm x 232 mm	4.40 dm ³	516.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.