# **OSRAM**

# ORIGINAL - METAL BASE -

Original spare part





#### The cost-effective original spare parts

ORIGINAL signal lamps with metal bases feature - like all ORIGINAL products from OSRAM - a reliable OEM quality. Due to the wide product range, the lamps can be used as original spare lamps for different applications.

#### Technical data

#### **Product information**

Order reference	3796	
Application (Category and Product specific)	Auxiliary lamp	


#### **Electrical data**

Power input	2 W
Nominal voltage	12.0 V
Nominal wattage	2.00 W
Test voltage	13.5 V
Power input tolerance	±8 %

#### Photometrical data

Luminous flux	12.5 lm
Luminous flux tolerance	±25 %

#### **Dimensions & weight**



Diameter	9 mm
Product weight	1.84 g
Length	23.9 mm

#### Lifespan

Lifespan B3	300 h
Lifespan Tc	750 h

#### Additional product data

Base (standard designation)	BA9s

#### Capabilities

Technology	AUX
Certificates & standards	
ECE category	
Approval marks – approval	-

# Order reference 3796

#### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300891309	OSRA3796	-	-	-
4050300891316	OSRA3796	-	-	-
4050300891309	OSRA3796	-	-	-

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300891309	ORIGINAL - METAL BASE 3796	Unpacked 1	- x - x -		
4050300891316	ORIGINAL - METAL BASE 3796	Folding carton box 10	46 mm x 29 mm x 112 mm	0.15 dm³	29.40 g
4008321095718	ORIGINAL - METAL BASE 3796	Shipping carton box 50	148 mm x 115 mm x 55 mm	0.94 dm <sup>3</sup>	176.50 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

1.0 ℃ 2. ⊂=□ ↔ [













