

---

# Product datasheet

## HALOLINE PRO 400 W 230 V R7S

HALOLINE PRO | Double ended halogen lamps with tube base



- General illumination Entrance lighting Pathway lighting  
Outdoor applications only in suitable luminaires Traffic areas Shops Restaurants, hotels and similar prestigious applications Offices, public buildings Ideal for emphasizing and accentuating the structure of a room

- Brilliant accent lighting Direct replacement for standard tubular halogen lamps Significantly lower CO2 emissions compared to standard version Lower thermal output (compared with the standard reference product) No transformer required Contains no mercury

## Product datasheet

### Technical data

#### Electrical data

Nominal wattage	400.00 W
Nominal voltage	230 V
Rated wattage	400.00 W
Claimed equiv. conventional lamp power	500 W

#### Photometrical data

Rated color temperature	2900 K
Light color (designation)	Warm White
Rated luminous flux	8750 lm
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.80
Nominal luminous flux	8750 lm
Color temperature	2900 K
Luminous flux	8750 lm

#### Light technical data

Starting time	0.0 s
---------------	-------

#### Dimensions & weight



Diameter	12.0 mm
Overall length	114.2 mm
Length	114.2 mm
Outer bulb	T12
Product weight	11.00 g
Maximum diameter	12.0 mm

## Product datasheet

### Lifespan

Rated lamp life time	2000 h
Number of switching cycles	50000

### Additional product data

Base (standard designation)	R7s
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357/For outdoor applications and operation in damp locations special approved fixtures are required

### Capabilities

Fuse, quick-acting	2.0 A
Burning position	Any
Dimmable	Yes

### Certificates & standards

Energy efficiency class	C
Energy consumption	400 kWh/1000h


### Country specific categorizations

ILCOS	HDG-400-230-R7s-114,2
Order reference	64702 400W 230V

## Product datasheet

### Light Distribution

---



HAL\_ohne\_UVS

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321207715	HALOLINE PRO 400 W 230 V R7S	Shipping carton box 20 Pieces Folding carton box	149 mm x 78 mm x 113 mm	1.31 dm <sup>3</sup>	328.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner  
of LEDVANCE of LAMPS

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany