
TUNGSRAM

Innovation is our heritage EST. 1896







Biax™ D/E LongLast™ 4pin, External Starter Req. F26W DBX/T4/840/4P TU 93105916

Product information

Biax™ D&D/E LongLast™ lamps are available in 10, 13, 18 and 26 watt ratings, 10 and 13W in T3 tube size, 18 and 26W in T4 tube size and ranging from 101mm to 174mm in length. Five colours are available in two-pin and four-pin caps. A high colour rendering index (CRI) of 82 gives rich, vibrant colour. The lamps are available in warm and cool colour temperatures suitable for a wide variety of environments.

Features

- Up to 80% energy saving versus normal incandescentlamps
- Lasts 10 times longerthan standard incandescentlamps
- High colourrendering index 82Ra
- Fullrange of colourtemperatures—2700, 3000, 3500,4000 and 6500K
- 4-pin lamps for use with electronic gear may be used with dimmers







Application areas

- Down lighting
- Corridorlighting
- Wall sconces in office buildings
- Hotels/motels
- Restaurants
- Retail

Application areas







Product data

Product Code	93105916
Bulb Shape	Quad plug-in
Bulb maximum overall diameter [mm]	34.4
Maximum Overall Length [mm]	162
Net weight per piece [g]	66
Gross weight per piece [g]	92
Operating position	U - Universal
Mercury Content [mg]	3
UV radiance	exempt
Brand	Tungsram
Cap/Base	G24q-3

Performance data

Colour Code	840
Rated Lumens [lm]	1800
Weighted energy consumption [kWh/1000h]	26.4
Energy efficiency class (EEC)	A
Rated Life [h]	12000
Rated median life on electronic (HF / ECG) ballast on IEC 12-hour cycle	20000
Rated median life on electronic (HF / ECG) ballast on IEC 3-hour cycle	17000
Nominal correlated colour temperature (CCT) [K]]	4000
Nominal lumens [lm]	1800
Colour Rendering Index (CRI) [Ra]	82



Electrical data


Rated power [W]	24.0
Operating Temperature (MIN) [°C]	-15
Starting ambient temperature range	-15
Dimming Capability	Yes
Nominal power [W]	26
Nominal lamp voltage [V]	105


Logistic data

Shipment	Standard
DUN Code	15994100010606
EAN Code	5994100010609
Pack Quantity	10
Inner pack type	BOX
Layer quantity	600 EUR, 750 UK
Layer quantity EUR	600
Layer quantity UK	750
Pallet quantity EUR (PC)	3000
Pallet quantity UK (PC)	3750
Outer case size	191 x 82 x 187 (mm)
Product status	Available



Technical drawing







Survival data



Downloads & Links

Go to the catalog site (HTTP)

Product family datasheet (PDF)

CFL Non-Integrated Spectrum Catalogue (PDF)

LongLast™ Biax™ D and D/E Data sheet (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

