

## **TUNGSRAM**

Innovation is our heritage EST. 1896









82 lumens/watt

Biax™ L LongLast™ 4-pin, External Starter Req. F34W BX/T5/835/4P TU 93105967

#### **Product information**

Biax™ L covers a range of single ended compact fluorescent lamps with high lumen output and are available in a wide range: 18, 24, 34, 36, 40, 55 and 80 watt versions. The single ended design is less than half the length of standard fluorescent lamps. This makes Biax™ L the ideal choice for modular luminaires. The range is available in colours of 2700, 3000, 3500, and 4000K allowing use in most environments. All Biax™ L lamps have a CRI of 82. The family of Biax™ L lamps offers a rated life\* of 10,000 hours for 18W to 36W and 20,000 hours for 40, 55 and 80W. The 40, 55 and 80W versions are for use on high-frequency electronic gear only.

at 3 hours per startLong single biaxial tubes

#### **Application areas**











# Biax™ L LongLast™ 4-pin, External Starter

Req. F34W BX/T5/835/4P TU 93105967

#### Product data

Product Code	93105967
Bulb Shape	Biax Plug-in
Bulb maximum overall diameter [mm]	43.8
Maximum Overall Length [mm]	538.8
Net weight per piece [g]	212
Gross weight per piece [g]	260
Operating position	U - Universal
Mercury Content [mg]	3
UV radiance	exempt
Brand	Tungsram
Cap/Base	2G11

#### Performance data

Colour Code	835
Rated Lumens [lm]	2800
Weighted energy consumption [kWh/1000h]	33.0
Energy efficiency class (EEC)	A+
Rated Life [h]	10000
Nominal correlated colour temperature (CCT) [K]]	3500
Nominal lumens [lm]	2800
Colour Rendering Index (CRI) [Ra]	82



# Biax™ L LongLast™ 4-pin, External Starter

Req. F34W BX/T5/835/4P TU 93105967

#### Electrical data

Rated power [W]	30.0
Operating Temperature (MIN) [°C]	-15
Starting ambient temperature range	-15
Dimming Capability	Yes
Nominal power [W]	34
Nominal lamp voltage [V]	120

## Logistic data

Shipment	Standard
DUN Code	15994100011115
EAN Code	5994100011118
Pack Quantity	25
Layer quantity	250 EUR, 350 UK
Layer quantity EUR	250
Layer quantity UK	350
Pallet quantity EUR (PC)	1000
Pallet quantity UK (PC)	1400
Outer case size	572 x 141 x 238 (mm)
Product status	Available




# Biax™ L LongLast™ 4-pin, External Starter Req. F34W BX/T5/835/4P TU

F34W BX/T5/835/4P TU 93105967

### Technical drawing










## Biax™ L LongLast™ 4-pin, External Starter

**Req.** F34W BX/T5/835/4P TU

93105967

#### Survival data



#### Downloads & Links

Go to the catalog site (HTTP)

CFL Non-Integrated Spectrum Catalogue (PDF)

LongLast™ Biax™ L Data sheet (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)