



154

kWh/1000h

A

energy class

64

lumens/watt

CSS

CSS150/CAP/50

88485

Product information

A 150W discharge lamp for use in moving lighting fixtures.

Application areas



Other



Product data

Product Code	88485
Light Center Length [mm]	30
Bulb Shape	Tubular
Bulb Finish	Clear
Bulb Diameter [mm]	16.5
Maximum Overall Length [mm]	48.64
Arc Gap	6
Net weight per piece [g]	10
Gross weight per piece [g]	13
Operating position	VBD - Vert Base Down
Brand	GE Lighting
Cap/Base	GY9.5

Performance data

Colour Code	850
Rated Lumens [lm]	9000
Weighted energy consumption [kWh/1000h]	154.0
Energy efficiency class (EEC)	A
Nominal chromaticity coordinate X	0.3
Nominal chromaticity coordinate Y	0.3
Nominal correlated colour temperature (CCT) [K]	5000
Nominal lumens [lm]	9000
Colour Rendering Index (CRI) [Ra]	80

Electrical data

Rated power [W]	140.0
Lamp Current [A]	1.87
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	140
Nominal lamp voltage [V]	85

Logistic data

DUN Code	10043168884850
EAN Code	0043168884853
Pack Quantity	10
Layer quantity	560 EUR, 720 UK
Layer quantity EUR	560
Layer quantity UK	720
Pallet quantity EUR (PC)	5040
Pallet quantity UK (PC)	5040
Outer case size	195 x 80 x 115 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

Disclaimer

Special Purpose Lamp, Not suited for household illumination

