



**633**  
kWh/1000h

**A**  
energy class

**70**  
lumens/watt

## Discharge - Double Ended Hot Restrike

CSR575/S/DE/70

70979

### Product information

Double ended compact source rare earth metal halide hot restrike lamps from GE can be used in a variety of applications requiring high luminance, reliability and excellent colour characteristics. Industry Standard outline with hot restrike capability- Dimmable with stable colour- High efficiency with excellent lumen maintenance.

### Application areas



Film and Broadcast



Event and Tour



### Product data

Product Code	70979
Bulb Shape	GLS
Bulb Finish	Clear
Bulb Diameter [mm]	21
Maximum Overall Length [mm]	138
Arc Gap	7
Net weight per piece [g]	34
Gross weight per piece [g]	130
Operating position	U - Universal
Brand	GE Lighting
Cap/Base	SFc10-4

### Performance data

Colour Code	770
Weighted energy consumption [kWh/1000h]	632.5
Energy efficiency class (EEC)	A
Nominal chromaticity coordinate X	0.307
Nominal chromaticity coordinate Y	0.309
Nominal correlated colour temperature (CCT) [K]	7000
Nominal lumens [lm]	40000
Colour Rendering Index (CRI) [Ra]	75

### Electrical data

Lamp Current [A]	6.1
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	575
Nominal lamp voltage [V]	95

## Logistic data

DUN Code	10043168709795
EAN Code	0043168709798
Pack Quantity	10
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	260 EUR, 330 UK
Layer quantity EUR	260
Layer quantity UK	330
Pallet quantity EUR (PC)	1040
Pallet quantity UK (PC)	1320
Outer case size	208 x 166 x 280 (mm)
Product status	Phased-out

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

## Disclaimer

Special Purpose Lamp, Not suited for household illumination

