
TUNGSRAM

Innovation is our heritage EST. 1896







LED Plug In 4Pin Gen2 LED 7.5/G2/G24q-2/4P/H/840 TU BX1/6 93110775

Product information

LED 4 Pin Plug-In lamp offers safe, reliable and affordable energy saving alternative to Compact Fluorescent 4 Pin Plug-In lamps used in downlight fixtures. The replacement can be completed without tools or costly upgrade. The new GEN2 4Pin LED Plug-In lamp is available in 7.5W and 10W to replace 18W (G24q-2) and 26W (G24q-3) regular CFL lamps. The new lamp is designed for horizontal applications.

Application areas







) Hospitality



LED Plug In 4Pin Gen2 LED 7.5/G2/G24q-2/4P/H/840 TU BX1/6 93110775

Product data

Product Code	93110775
Bulb maximum overall diameter [mm]	34.5
Maximum Overall Length [mm]	162
Net weight per piece [g]	125
Gross weight per piece [g]	147
Operating position	Horizontal
Mercury Content [mg]	0mg
RoHS compliant	Yes
Brand	Tungsram
Cap/Base	G24q-2

Performance data

Nominal/ Rated Beam Angle [°]	110 x 120
Color consistency (SDCM)	<6 step
Rated Lumens [lm]	880
Weighted energy consumption [kWh/1000h]	8.25
Rated efficacy [lm/W]	117.33
Energy efficiency class (EEC)	A+
Rated life L70/B50 [h]	50000
Power factor	Ballast driven
Nominal correlated colour temperature (CCT) [K]]	4000
Nominal lumens [lm]	880
Colour Rendering Index (CRI) [Ra]	80



LED Plug In 4Pin Gen2 LED 7.5/G2/G24q-2/4P/H/840 TU BX1/6 93110775

Electrical data

Nominal lamp power factor	Ballast driven
Rated power [W]	7.5
Operating Temperature [°C]	-20C +40C
Operating Temperature (MIN) [°C]	-20
Operating Temperature (MAX) [°C]	40
Startup time [sec]	<0.5
Number of switching cycles	30000
Dimming Capability	No
Nominal power [W]	7.5

Logistic data


Shipment	Standard	
DUN Code	15994100028212	
EAN Code	5994100028215	
Pack Quantity	6	
Inner pack type	Bx	
Outer pack type	outer bx	
Layer quantity	EL 600 / UL 672	
Layer quantity EUR	600	
Layer quantity UK	672	
Pallet quantity EUR (PC)	3600	
Pallet quantity UK (PC)	4032	
Outer case size	118 x 80 x 178 mm	
Product status	Available	





LED Plug In 4Pin Gen2 LED 7.5/G2/G24q-2/4P/H/840 TU BX1/6

LED 7.5/G2/G24q-2/4P/H/840 TU BX1/6 93110775

Light distribution







Downloads & Links

Go to the catalog site (HTTP)

Photometry (IES)

Product datasheet (PDF)

Product datasheet (FR) (PDF)

Images (HTTP)

LED PlugIn compatibility ballasts (HTTP)

Datasheet (FR) (PDF)

Tungsram is a registered trademark of