

15

kWh/1000h

A+

energy class

101

lumens/watt

## LED Stik

LED15/STIK/830/220-240V/B22/BX TU  
93096456

## Product information

LED Stik illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb and some sockets where a traditional bulb or CFL doesn't fit. Replace a 40W, 60W, 75W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years\*. That's a long time you can spend not worrying about light bulbs.

### Features & benefits

- LED technology for energy saving
- Redesigned shape with multiple advantages:
- To fit in more fixtures compared to CFL
- Optimised for omni-directional light distribution
- Space-saving benefits on-shelf
- 240 degree Beam angle
- Replaces a standard 40W, 60W, 75W & 100W bulb
- Rated life of 15 years\*
- 3 colour options - 3000K, 4000K & 6500K
- Always ready - instant brightness
- No mercury - worry-free use and disposal
- Warranty: 2 years with maximum 8 000 burning hours

according to Tungsram Standard Warranty conditions

- Based on 2.7 hours of per day use.
-

## Product data

|                                    |           |
|------------------------------------|-----------|
| Product Code                       | 93096456  |
| Bulb Shape                         | T45       |
| Bulb Finish                        | White     |
| Bulb maximum overall diameter [mm] | 45        |
| Nominal Length [mm]                | 135.5     |
| Net weight per piece [g]           | 75        |
| Dimmability                        | No        |
| RoHS compliant                     | Yes       |
| Brand                              | Tungsramp |
| Cap/Base                           | B22       |

## Performance data

|   |       |
|---|-------|
| Nominal/ Rated Beam Angle [°]                   | 240   |
| Rated Lumens [lm]                               | 1521  |
| Weighted energy consumption [kWh/1000h]         | 15.0  |
| Rated efficacy [lm/W]                           | 101.4 |
| Energy efficiency class (EEC)                   | A+    |
| Rated life L70/B50 [h]                          | 15000 |
| Nominal correlated colour temperature (CCT) [K] | 3000  |
| Nominal lumens [lm]                             | 1521  |
| Colour Rendering Index (CRI) [Ra]               | 80    |


## Electrical data

|   |            |
|---|------------|
| Operating Temperature (MIN) [°C]            | -20°C      |
| Operating Temperature (MAX) [°C]            | +40°C      |
| Starting time (sec)                         | <0,5 s     |
| Power Factor                                | >0.5       |
| Warm up time up to 60% of full light output | Instant on |
| Number of switching cycles                  | 50k        |
| Nominal lamp voltage range [V]              | 220-240V   |
| Nominal power [W]                           | 15         |

## Logistic data

|                |                |
|----------------|----------------|
| Shipment       | Standard       |
| DUN Code       | 20064894509036 |
| EAN Code       | 0064894509032  |
| Pack Quantity  | 15             |
| Product status | Available      |

## Light distribution



## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Photometry \(IES\)](#)

[Product datasheet \(PDF\)](#)

[Product datasheet \(FR\) \(PDF\)](#)

[Datasheet \(PDF\)](#)

[Images \(HTTP\)](#)

[DoC document \(PDF\)](#)

[DoC document - E14 \(PDF\)](#)

[Datasheet \(FR\) \(PDF\)](#)

