
TUNGSRAM

Innovation is our heritage EST. 1896








PAR 36 25PAR36/WFL 12V 14555

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- · Choice of beam widths
- · Excellent colour rendering
- High efficiency combined with low operating costs
- · Robust and reliable
- UV control
- Easy retrofit
- · Colour consistent throughout life
- · Colour blends with halogen and fluorescent

Application areas









Product data

Product Code	14555
Bulb Shape	PAR
Bulb Finish	Aluminized
Bulb Diameter [mm]	114.3
Maximum Overall Length [mm]	69.9
Net weight per piece [g]	248
Gross weight per piece [g]	250
Brand	GE Lighting
Cap/Base	Screw terminal

Performance data

Nominal/ Rated Beam Angle [°]	30
Nominal center beam candlepower (CBCP) [cd]	500
Rated Lumens [lm]	90
Weighted energy consumption [kWh/1000h]	26.5
Useful lumens (at 90° cone) [lm]	90
Energy efficiency class (EEC)	E
Rated Life [h]	2000
Nominal correlated colour temperature (CCT) [K]]	2700
Nominal lumens [lm]	150

Electrical data

Rated power [W]	25.0
Coil type	C-6
Ballast Required	Yes
Nominal power [W]	25
Nominal lamp voltage [V]	12



Logistic data

DUN Code	00043168145558
Pack Quantity	12
Layer quantity	1 UK
Layer quantity UK	1
Pallet quantity UK (PC)	1200
Outer case size	226 x 211 x 313 (mm)
Product status	Phased-out

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.