
TUNGSRAM

Innovation is our heritage EST. 1896





500 kWh/1000h energy class


PAR 64 CP87 - Q500PAR64/NSP 230V 93106680

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- · High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- · Colour blends with halogen and fluorescent

Application areas





Product data

Product Code	93106680
Light Center Length [mm]	80
Bulb Shape	PAR
Bulb Diameter [mm]	204
Maximum Overall Length [mm]	150
Net weight per piece [g]	821
Gross weight per piece [g]	1072
Brand	Tungsram
Cap/Base	GX16d

Performance data

Nominal center beam candlepower (CBCP) [cd]140000Rated Lumens [lm]6500Weighted energy consumption [kWh/1000h]500.0Useful lumens (at 90° cone) [lm]6500Energy efficiency class (EEC)CRated Life [h]300Nominal correlated colour temperature (CCT) [K]]3200Colour Rendering Index (CRI) [Ra]100	Nominal/ Rated Beam Angle [°]	19
Weighted energy consumption [kWh/1000h]500.0Useful lumens (at 90° cone) [lm]6500Energy efficiency class (EEC)CRated Life [h]300Nominal correlated colour temperature (CCT) [K]]3200	Nominal center beam candlepower (CBCP) [cd]	140000
Useful lumens (at 90° cone) [lm]6500Energy efficiency class (EEC)CRated Life [h]300Nominal correlated colour temperature (CCT) [K]]3200	Rated Lumens [lm]	6500
Energy efficiency class (EEC)CRated Life [h]300Nominal correlated colour temperature (CCT) [K]]3200	Weighted energy consumption [kWh/1000h]	500.0
Rated Life [h]300Nominal correlated colour temperature (CCT) [K]]3200	Useful lumens (at 90° cone) [lm]	6500
Nominal correlated colour temperature (CCT) [K]] 3200	Energy efficiency class (EEC)	C
	Rated Life [h]	300
Colour Rendering Index (CRI) [Ra] 100	Nominal correlated colour temperature (CCT) [K]] 3200	
	Colour Rendering Index (CRI) [Ra]	100

Electrical data

Rated power [W]	500.0
Coil type	C-13
Dimming Capability	Yes
Ballast Required	No
Nominal power [W]	500
Nominal lamp voltage [V]	230

Logistic data

DUN Code	15994100021947
EAN Code	5994100021940
Pack Quantity	6
Layer quantity	24 EUR, 30 UK
Layer quantity EUR	24
Layer quantity UK	30
Pallet quantity EUR (PC)	120
Pallet quantity UK (PC)	150
Outer case size	536 x 391 x 196 (mm)
Product status	Available

Downloads & Links Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP)

Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.



Tungsram is a registered trademark of Tungsram Operations Kft.

tungsram.com

We in Tungsram Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungsram cannot accept any liability arising from the reliance on such data to the extent permitted by law.