



68  
kWh/1000h

A  
energy class

90  
lumens/watt


## T8 Polylux XLR™ - G13 Cap

FT8 58W 840 TU SL1/25

93096233

### Product information

Polylux XLR™ lamps should be the natural choice for all fluorescent lighting applications. The excellent colour reproduction flatters skin tones making people appear more natural, and makes merchandise appear more vibrant and colourful.



## Product data

Product Code	93096233
Bulb Shape	Tubular
Bulb Finish	Coated
Regulatory comment	CE Certified
Bulb maximum overall diameter [mm]	28
Maximum Overall Length [mm]	1514.2
Cap to Cap Length (Max) [mm]	1500
Mercury Content [mg]	<3,5mg
RoHS compliant	Yes
Brand	Tungsrasm
Cap/Base	G13

## Performance data

Colour Code	840
Rated Lumens [lm]	5220
Weighted energy consumption [kWh/1000h]	67.09
Rated efficacy 25°C EM preheat	90
Energy efficiency class (EEC)	A
Rated lumen maintenance factor (2000 hours)	0.97
Rated lumen maintenance factor (4000 hours)	0.95
Rated lumen maintenance factor (6000 hours)	0.94
Rated lumen maintenance factor (8000 hours)	0.93
Rated lumen maintenance factor (12000 hours)	0.92
Rated lumen maintenance factor (16000 hours)	0.9
Rated lumen maintenance factor (20000 hours)	0.9
Operating mode for LSF and LLMF data	HF
Rated Life [h]	{EM 3-hour} : 15000
Rated survival factor (2000 hours)	1
Rated survival factor (4000 hours)	1
Rated survival factor (6000 hours)	0.99
Rated survival factor (8000 hours)	0.99
Rated survival factor (12000 hours)	0.98
Rated survival factor (16000 hours)	0.9
Rated survival factor (20000 hours)	0.5
Rated median life on electromagnetic (EM / CCG) ballast on IEC 12-hour cycle	18000
Rated median life on electronic (HF / ECG) ballast on IEC 12-hour cycle	23000
Rated median life on electronic (HF / ECG) ballast on IEC 3-hour cycle	20000
Nominal correlated colour temperature (CCT) [K]	4000
Nominal lumens [lm]	5220
Colour Rendering Index (CRI) [Ra]	80

## Electrical data

Rated power [W]	58.0
Lamp Current [A]	0.670A
Design Lamp ambient temperature [°C]	25
Starting ambient temperature range	-15°C ...50°C
Dimming Capability	Yes
Nominal power [W]	58

## Logistic data

Shipment	Standard
DUN Code	15994100016462
EAN Code	5994100016465
Pack Quantity	25
Inner pack type	sleeve
Outer pack type	outer box
Product status	Available

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)